

BIO PRODUCTS AUSTRALIA PTY LTD

ABN 12007959775

25 Aldgate Terrace, Bridgewater / South Australia 5155

Telephone 08-83391923 Facsimile 08-83395799

BIO ALL PURPOSE VARNISH

- interior -

DESCRIPTION : A transparent varnish in gloss or satin providing a colourless, hard but flexible dirt- and water-repellent finish. It is sweat and saliva proof. For use on all interior timber surfaces, such as windows, banisters, furniture, toys, ceilings and paneling. Not recommended for constantly humid environments such as bathrooms and laundries. Note: for timber flooring see BIO Floor Varnish

PREPARATION : Do not apply coatings to unseasoned or wet timber. Wood should be well sanded, dry and cleaned of greasy, waxy and dirty contaminants using BIO Thinner. Round off sharp edges. It is also good practice to prime back surfaces. Hardwoods and timbers rich in natural oils, waxes, acids and terpenes should be degreased using Bio Thinner, because these substances may mix with the varnish and prolong its drying time. Let dry for 24 hours. Imperfect coats may require complete stripping before applying BIO Products.

PRIMING: Baltic Pine and Pinus Radiata: Prime with one coat of Priming Oil. Remove excess oil after 15-30 minutes. Allow drying for 24 hours, and then applying Bio All Purpose Varnish.

APPLICATION : Stir thoroughly before use with a broad flat stirrer. Thin with 10-20% BIO Thinner to obtain a smooth flowing consistency. Brush thinly and evenly, working varnish well into the grain. Thick coats wrinkle when dry. Maintain a wet edge when painting. Avoid bubbles. Allow 12 to 24 hours to dry between coats. Lightly sand between coats if necessary with fine sandpaper. Apply the second and subsequent coats only after the previous coat has thoroughly dried. Low temperature and humid conditions prolong the drying time. Do not paint below +10C and or above 80% humidity, in cold damp conditions, when condensation, rain, dew or frost are likely to occur or hot days, direct sunlight and hot surfaces. Provide adequate ventilation during application and drying. Reaches maximum durability after 21 days.

CLEANING : Use BIO Thinner.

COVERAGE : 1 Litre covers 15-18 sqm., depending on the absorbency of the timber.

PACKAGING : 1Litre and 4 Litres

INGREDIENTS : Based on tung oil, pine resin, wax, essential oils, paraffin oil, quartz, bentone, lead free drying agents.

STORAGE : Keep tightly sealed in a cool and dry place. Surface film may develop in opened cans.

PAINT DISPOSAL: Do not pour left over paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Let empty container dry out as well and dispose via recycling program.

PRECAUTION : Keep away from open flames and out of the reach of children. Please dispose used rags in a sealed metal container. Can spontaneously combust.

The preceding information is given as a general guide only. Some variations may occur or be advisable for particular conditions. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

BIO ALL PURPOSE VARNISH is an environmental friendly product.

1/08/2007