

VOLVOX CLAY DÉCOR

DESCRIPTION: Solvent free, non-drip, long-lasting interior wall and ceiling paint. Clay Decor can be applied to most interior surfaces such as Gyprock, timber, masonry, brick and fibre cement without priming. Clay Décor can be used exterior in frost free regions and water protected areas. VOLVOX Clay Decor is permeable to vapour and absorbs variations in humidity providing a more comfortable and healthy living environment. Due to its high proportion of solids VOLVOX Clay Decor covers exceptionally well (99.55%).

Clay Colours & Sizes

Mont Blank (White) 5 & 10 litre

Ivory (Off White) 5 litre

Dacar (Ochre) 4 litre

Sienna (Orange) 4 litre

Terracotta (Red) 4 litre

Polar (Green) 4 litre

Smoke (Grey) 4 litre

ENVIRONMENT AND HEALTH FEATURES: Clay Decor is made from natural and non-toxic raw materials. Manufacturing process ensures ecological sustainability and avoids water pollution. The product will not charge electro static energy. When used according to manufacturer's direction, the product is harmless to human and the environment. Certified EU Eco-Label Licence No.: UK 7/1

SURFACE PREPARATION: Remove dirt, grease, oil and loose, peeling and flaking material. Fill cracks and holes with a filler. Sand the surface smooth after and remove all dust. Sandy and powdery surfaces should be primed with suitable primer such as VOLVOX Lasur Binder. Stains, water marks, nicotine etc. must be treated with a suitable oil based priming paint. Light sanding is recommended when painting over glossy or semi-gloss surfaces. Prime all metallic surfaces using a metal primer first. Mould and fungus must be permanently removed before applying VOLVOX Clay Decor.

APPLICATION: Generally apply two coats of VOLVOX Clay Decor by roller, brush or spray. Spread the Decor evenly in all directions. On light coloured even surfaces one coat is sufficient. On very absorbent surfaces such as Gyprock, plaster, sandstone etc. application may be eased by dampening the surface with water and/or reducing the first coat with up to 5% water. Allow each coat to dry completely before re-painting. Do not apply in temperatures below 10°C or above 25°C. For a good finish ensure any dry paint around lid is not allowed to drop into the paint when opening, if necessary strain paint. It is very



sales@coloursbynature.com.au

www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550

important to stir paint well prior to each application using a mechanical stirring device, for example, a commercial stirrer attached to powerful slow speed power drill. Do not use paint equipment, in particular rollers and brushes that have been previously used with conventional synthetic paints.

DRYING AND RECOATING: VOVOX Clay Decor will normally dry within 2–6 hours and may be recoated after. In cold or humid conditions drying time may be lengthened. VOLVOX Clay Decor will be completely dry and cured after 10 days.

COVERAGE: 1 litre will cover up to 8 sq. Metres depending on texture and porosity of surface.

CLEAN UP: With water away from drains.

INGREDIENTS: Water, clay coming from various pits, chalk, kaolin, vinegar ester, methylcellulose, titanium dioxide (White Clay Décor only), 0.1% synthetic preservatives

SAFETY: Even if non-toxic, Clay Decors should be kept out of reach of children.

STORAGE AND SHELF LIFE: Store tightly sealed in a cool and dry place. Minimum shelf life for unopened and properly stored cans is 24 months. Protect against frost.

DISPOSAL: Allow unwanted Clay Decor to dry. Solid matter should be disposed of via the normal garbage collection service.

COLOURMIXING: All clay colours can be intermixed and coloured with pigments, pigments pastes and most commercial tints in the Natural Colouring System (NCS) **Note:** To maintain washability as well as a smooth and even surface, not more than 5 – 8% of pigments should be added. If more pigmentation is desired, seal painted surface using a suitable sealer such as VOLVOX Wax Finish or VOLVOX Lasur Binder after VOLVOX Clay Décor is completely dry.

WORKING WITH CLAY DECOR: Clay Decor can be applied in the traditional condensing technique. Clay Decor is applied thickly and burnished with the edge of a plastic trowel or spatula 5 – 20 minutes after. The friction and pressure draws the water to the surface and creates a level of polish commensurate with the effort. Sand smooth when completely dry and then apply VOLVOX Wax Finish. Clay Décor can also be modified with fine clean sand or clay powder or lime for more decorative finishes such as “Tadelakt”. Always make a test patch before starting work. This technical information sheet is intended to provide guidelines for users. Products are guaranteed to give satisfactory performance only if used as recommended. Liability shall be limited to refund of purchase price or the replacement of a defective product. There are no other warranties expressed or implied.



sales@coloursbynature.com.au
www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550

Disclaimer: The user is recommended to test the product on the intended surface to ensure its suitability. Made in Germany



sales@coloursbynature.com.au

www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550