

## LIVOS GLEIVO LIQUID BEESWAX INTERIOR

**RANGE OF APPLICATION:** Interior timber such as panelling and furniture after pre-treatment with compatible products. Not suitable for moist areas. For regular care of linoleum. To refresh waxed timber, cork and stone surfaces, like floors, panelling and furniture.

**TECHNICAL QUALITIES:** Liquid. Anti static finish. Suitable for airless spraying device. Silky gloss finish.

**FULL DECLARATION:** Beeswax, micronized wax, carnauba wax, pine oil, linseed oil, orange oil, Isoaliphates, alumina, rosemary oil and drying agents free of lead.

**COVERAGE:** For surface treatment: 1litre is sufficient for approximately 25 m<sup>2</sup>, i.e. 40 ml/m<sup>2</sup>. Coverage could be considerably less depending upon the condition and absorbency of the surface. Always do a test application! For surface care: 1litre is sufficient on average for 100 m<sup>2</sup>, i.e. 10 ml/m<sup>2</sup>.

**COLOUR:** Clear. Tinting is possible with a maximum of 10 % VINDO Coating Varnish No. 629.

**DILUTION:** Delivered ready to use.

**CLEAN UP:** Clean equipment immediately after use with LIVOS SVALOS Dilutant/Thinner.

**DRYING TIME:** At 23°C and 50 % relative humidity, approximately 2 - 4 hours.

**SPECIFIC GRAVITY:** 0.78 g/ml.

**SIZES:** 250ml\*; 1litre\*; 2.5litre; 10litre; 30litre; 200litre.\*typical sizes stocked from Colours by Nature

**STORAGE:** Cool and dry, please see label for expiration date. Close lid tightly after use.

**PREPARATION:** The surface must be dry, solid, clean, and free of grease and dust. Surface should be pre-treated with compatible natural timber oil, like MELDOS Natural Resin Hardening Oil No. 264, ARDVOS Wood Oil No. 266 or stains like KALDET Transparent Wood Stain.

If the surface has been previously treated with products from another manufacturer, do a test application of GLEIVO on an inconspicuous spot to ensure compatibility.



[sales@coloursbynature.com.au](mailto:sales@coloursbynature.com.au)  
[www.coloursbynature.com.au](http://www.coloursbynature.com.au)

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550

**APPLICATION:** Shake or stir product thoroughly before using. Apply GLEIVO Beeswax No. 315 very thinly and evenly with a brush or cloth. After approximately 2 - 4 hours, polish (in the direction of the wood grain of the timber) with a wadded cloth, a wax brush or a floor polisher.

**VARIATION OF USES:**

**SAFETY ADVICE:** Safety advice contains limonene. S2 Keep out of the reach of children. S62 If swallowed, do not induce vomiting: seek medical advice immediately and show the container or label.

**DISPOSAL:** According to locally regulated laws.

**PACKAGING:** Glass or made of polyethylene (PE). Both materials are ground water neutral and recyclable.

**IMPORTANT TIPS:** A very thin treatment of beeswax applied to surfaces with a high electrostatic charge (for example; artificial resin varnishes, etc.) can significantly reduce static electricity on those surfaces. Ensure good ventilation during application and drying times. Clean soiled surfaces with TRENA Neutral Cleaner No. 556 or SVALOS Dilutant No. 222 or BIO Thinner before applying GLEIVO No. 315.

LIVOS products contain organically sourced ingredients and are never tested on animals.

These directions were prepared by LIVOS and Colours by Nature and are the result of long years of research and practical testing. They are backed by LIVOS's most current expert information. New findings may invalidate this information. This information sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

Ref: Apr 2005 v1.3



[sales@coloursbynature.com.au](mailto:sales@coloursbynature.com.au)

[www.coloursbynature.com.au](http://www.coloursbynature.com.au)

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550