

VOLVOX HARD OIL WAX FINISH INTERIOR

DESCRIPTION: VOLVOX Hard Oil-Wax Finish a thick running oil-wax combination for fine sanded wood surfaces and cork interior. The product enhances the look and feel of natural wood and dries to a satin-matt sheen. This water-repellent floor & furniture finish is also suitable for kitchens and bathrooms.

DIN 53 160 certified for colour fastness when exposed to perspiration and saliva. DIN EN 71 Part 3 certified as suitable for toys.

ENVIRONMENT AND HEALTH FEATURES: VOLVOX Hard Oil Wax Finish is made from natural and non-toxic raw materials. The product is VOC free, it contains no solvents. Manufacturing process ensures ecological sustainability and avoids water pollution. The product will not charge electro static energy. When used according to manufacturer's direction, the product is harmless to human and the environment.

SURFACE PREPARATION: Provide a clean, dry, firm and grease free surface. Timber should be in good physical shape, absorbent and sanded to 100 -120 grid. Oil-, resin- and tannin-rich wood should be cleaned using appropriate methods.

APPLICATION: Stir well so the gel like Hard Oil Wax becomes fluid. Apply very sparingly and even.

VARIATION OF USES:

Do not apply in temperatures below 10°C or above 30°C.

DRYING AND RECOATING: Depending on temperature and humidity, dry to repaint after 6-12 hours.

Note: Estimate drying time by test application on cork.

CLEAN: UP: For cleaning tools use warm soapy water or Iso-paraffin thinner.

PACKAGING AND COVERAGE: 1 litre will cover 30-50 m² per coat. Sizes 0,75 litre and 2,5 litre

STORAGE AND SHELF LIFE: Store tightly sealed in a cool and dry place. Minimum shelf life for unopened and properly stored cans is 24 months.



sales@coloursbynature.com.au
www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550

INGREDIENTS: Flax Seed Oil, Tung Oil, Colophony, Bees Wax, Carnauba Wax, Lead-free dryers (Zircon, Cobalt Octoat), Oximes (Anti-skinning Agent). Product does not contain solvents

SAFETY: Always work in a well-ventilated area. Working rags and other fabrics soaked with oil may self-ignite. Let dry safely outdoors on a cloth line or store in a sealed metal container. The product by itself will not self-ignite.

Even if non-toxic, keep away from children.

DISPOSAL: Allow unwanted paint to dry. Solid matter should be disposed of via the normal garbage collection service.

DISCLAIMER: The user is recommended to test the product on the intended surface to ensure its suitability. This technical information sheet is intended to provide guidelines for users. Products are guaranteed to give satisfactory performance only if used as recommended. Liability shall be limited to refund of purchase price or the replacement of a defective product. There are no other warranties expressed or implied.

MAINTENANCE: In the first 3 weeks no water please! Use dry cleaning methods only such as dusting or brooming. Sand, moisture and dirt may harm your freshly treated timber. After that a damp (not wet) mopping may follow if necessary. Remove water splashes and staining liquids immediately. Remember that the oil-resin-wood layer must cure before full strength is achieved for sometimes many weeks.

Use only products that are suitable for cleaning and maintaining natural oil finished timber. We recommend VOLVOX Wood Soap, VOLVOX Wax Finish or/and VOLVOX Floor Renovator as an additive to mopping water. Avoid abrasive chemicals since these will attack the oil-resin-wood layer. From time to time, some drops of the original used oil can work miracles. Simply wipe a few drops to the timber. Wipe the surface dry after 10 -15 minutes.

Made in Germany



sales@coloursbynature.com.au

www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550