

VOLVOX TIMBER DECK FINISH EXTERIOR

DESCRIPTION: Ready to use Decking Oil for regular care and maintenance of hard- and softwood timber decks, hand rails, pergolas, garden furniture and other exterior timber surfaces. VOLVOX Timber Deck Care is based on high grade cold pressed flax seed oil with deep impregnating effect. Retaining vapour permeability of wood, VOLVOX Timber Deck Care prevents the building up of vapour pressure in Australian hardwood. Flaking or peeling is not possible. VOLVOX Timber Deck Care has been formulated to withstand the damaging effects of ultraviolet radiation. VOLVOX Timber Deck Care is a transparent, wood grain enhancing, and wear and tear resistant natural oil impregnation, recommended for traffic exposed exterior timber decks.

ENVIRONMENT AND HEALTH FEATURES: VOLVOX Timber Deck Care is made from natural and non-toxic raw materials. Solvent and VOC free. Manufacturing process ensures ecological sustainability and avoids water pollution. The product will not charge electro static energy. When used according to manufacturer's direction, the product is harmless to human and the environment.

SURFACE PREPARATION: Provide a clean, dry, firm and grease free surface. Timber should be in good physical shape. Old wood should be sanded in order to remove dead wood particles.

APPLICATION: Stir well. Apply one coat of VOLVOX Timber Deck Care using an oil broom, floor applicator or a soft paint brush. After 30 minutes saturation time remove all oil from the surface with a lint free cloth. This is to prevent tacky and glossy spots. Let dry for 12 hours.

Do not apply in temperatures below 10°C or above 30°C.

VARIATION OF USES:

DRYING: Depending on temperature and humidity, dry after 24 hours.

CLEAN UP: For cleaning tools use VOLVOX Iso-paraffin Thinner or plenty of soapy water.

PACKAGING AND COVERAGE: Depending on absorption of wood, 1 litre will cover 10-20 m² per coat. Sizes: 0.75L, 2.5L

STORAGE AND SHELF LIFE: Store tightly sealed in a cool and dry place. Minimum shelf life for unopened and properly stored cans is 24 months.



sales@coloursbynature.com.au
www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550


INGREDIENTS: Highest Grade, organically grown, cold pressed Flax Seed Oil, Pigments, Lead-free Dryers (Zircon, Cobalt Octoat), Essential Oils.

SAFETY: Always work in a well-ventilated area. Working rags and other fabrics soaked with oil may self-ignite. Let dry safely outdoors on a cloth line or store in a sealed metal container. The product by itself will not self-ignite. Even if non-toxic, keep away from children.

DISPOSAL: Allow unwanted paint to dry. Solid matter should be disposed of via the normal garbage collection service.

CARE & MAINTENANCE: Check Volvox Timber Deck Care treated surfaces from time to time and clean as necessary. If water repels, that's an indication that the surface is intact, if it doesn't it is time to apply another coat. Clean surface and proceed as above. This technical information sheet is intended to provide guidelines for users. Products are guaranteed to give satisfactory performance only if used as recommended. Liability shall be limited to refund of purchase price or the replacement of a defective product. There are no other warranties expressed or implied.

DISCLAIMER: The user is recommended to test the product on the intended surface to ensure its suitability. Made in Germany



Colours by Nature
as nature intended



sales@coloursbynature.com.au

www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550