

LIVOS ALIS DECKING OIL

Range of application: Teak, Bankirai, Larch, Douglas pine, Cedar. For exterior use only. For first treatment and maintaining.

Technical qualities: Produces a water repellent, open-pored finish. Fast drying, refreshes. No chipping or flaking. Surface finish is even and easy to maintain.

Full declaration: Linseed oil, wood oil, linseed oil - wood oil - stand oil, orange oil, Isoaliphates, linseed oil - stand oil - natural resin ester, earth - and mineral pigments and drying agents free of lead.

Colours: 048 chestnut 1 072 oak 554 oregon pine 1 Corresponds with the colour tone of many exotic hardwoods.

Application method: By brush or roller. (See reverse for further information)

Coverage: Exotic hardwoods, robinia, oak: First coat, 1 litre (1.06 fl. quart.) is sufficient for approximately 28 m² (301 ft²). Second coat, 1 litre is sufficient for approximately 40 m² (431 ft²).

Soft wood: First coat, 1 litre (1.06 fl. quart.) is sufficient for approximately 20 m² (215 ft²). Second coat, 1 litre is sufficient for approximately 28 m² (301 ft²).

On profiled wood the consumption can be up to 3 times higher. A test coat is recommended!

Drying time: At 23°C (73°F) and a relative humidity of 50% appx. 5 - 8 hours at good light- and ventilation conditions. Second coat after 18 hours drying time.

Specific gravity: Appx. 0.87 g/ml.

Safety advice: Contains limonene, May cause sensitisation by skin contact, Keep out of the reach of children. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Irritant.

Disposal: According to locally regulated laws.

Container sizes: 0.25 lt; 0.75 lt; 2.5 lt.



sales@coloursbynature.com.au

www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550

Storage Cool and dry please see label for expiry date. Always be sure to store and dispose cleaning cloths, polishing pads, sponges, etc That are still wet or even slightly moist with ALIS Decking Oil No. 579 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content in the product. The product alone will not undergo spontaneous combustion.

HOW TO USE

Preparation: The surface must be able to absorb, solid, clean, dry and free of dust.

Application: Apply 2 coats by brush in the direction of the wood grain at temperatures above 10°C (50°F). After 5 — 10 minutes spread out any unabsorbed product. Apply sparingly, surface must not be sticky. Alternatively with roller, spreading out unabsorbed product with brush. Before using, always test product on an inconspicuous spot to check compatibility with the existing surface and previously applied polishes or maintaining products. Refresh with ALIS Decking Oil at least 1 time a year or as required.

Important tips: Please treat strongly weathered exterior areas, such as porch floorings or wooden fences only after complete drying of the wood. As Bangkirai and Teak lose their moisture very slowly, treat these timbers in the dry season only. Protect the dry decking against dew by covering with a tarpaulin the evening before. Odour forming possible, until drying is complete.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction.

No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.



sales@coloursbynature.com.au

www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550