

LIVOS BIVOS OIL WAX

Range of application: For interior timber after pre-treatment with LIVOS products. For maintaining of previously waxed or oiled timber; for restoration of old furniture or wood carvings. For the care of KERA Cotto and linoleum.

Technical qualities: Transparent, velvet gloss, moisture-resistant, antistatic finish. DIN EN 71 Part 3 certified.

Full declaration: Linseed oil, linseed oil - stand oil - natural resin ester, linseed oil - stand oil, orange oil, Isoaliphates, beeswax, micronized wax, carnauba wax, pine oil, alumina, rosemary oil and drying agents free of lead.

Colour: Clear. Tinting is possible by adding a maximum of 10% of VINDO Natural Oil Paint No. 629.

Dilution: Delivered ready to use.

Application method: Brush, roller, spraying device, or with a wadded cloth.

VARIATION OF USES:

Coverage: 1 litre (1.06 fl. quart.) is sufficient for approximately 100 m² (1076 ft²), i.e. 10 ml/m², when applying with a wadded cloth and pre-treated surfaces. 1 litre (1.06 fl. quart.) is sufficient for up to 167 m² (1800 ft²), i.e. 6 ml/m², for other modes of application. Coverage could be considerably less depending upon the condition and absorbency of the surface. Always do a test application.

Drying time: Application with a wadded cloth approximately 20 - 30 minutes at 23^oC and 50% relative humidity. A drying time of 30 -120 minutes is required when applying by spraying device. All other application methods 24 hrs.

Cleaning up: Clean equipment immediately after use with SVALOS Dilutant No. 222.

Specific gravity: 0.84 g/ml.

Safety Advice: Always be sure to store cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with BIVOS-Oil-Wax No. 375 in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the vegetable oil content in the product contains limonene.



sales@coloursbynature.com.au
www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550

Keep out of the reach of children. If swallowed, do not induce vomiting: Seek medical advice immediately and show the container or label.

Disposal: According to locally regulated laws.

Container Size: 0.05 l; 0.125 l; 0.25 l; 0.75 l; 2.5 l; 10 l; 30 l; 200 l.

Storage: Cool and dry, please see label for expiration date. Close lid tightly after use, transfer unused portion of product to a smaller container for storage.

How to use BIVOS Oil Wax No. 375

Preparation: The surface must be dry, solid, clean, and free of grease and dust. Pre-treat timber with LIVOS oils or stains like MELDOS Natural Resin Hardening Oil No. 264, ARDVOS Wood Oil No. 266, GORMOS Wax Oil No. 267 or DARIX Transparent Wood Stain No. 297.

Application: Stir or shake product thoroughly before using. Apply very thinly; it is best to use a cloth to rub the product in vigorously. Polishing the surface after treatment is not necessary. With other application methods such as spraying, careful attention must be paid to applying a very thin and even coat. Excess product should be removed with a cloth. After 20 - 30 minutes of drying time, polish surface with a brush or a clean cloth. 1- 2 hours after polishing, surface will be dry to the touch.

Industrial application: via spraying and brush techniques (please request technical advice if necessary).

Renovation: Pre-treat the surface with the recommended LIVOS products, then apply BIVOS Oil Wax No. 375. Always test for compatibility with existing surface coatings before use.

LIVOS products contain organically sourced ingredients and are never tested on animals.



sales@coloursbynature.com.au

www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550