

LIVOS DONNOS PENETRATING FENCE STAIN EXTERIOR

Range of application: Exterior wood surfaces such as fences, sandboxes, outdoor toys, flower boxes, hotbeds, barns, and stables.

Technical qualities: Varnishing, water-repellent, weather resistant, open-pored, permeable to water vapour. Penetrates deeply, remains permanently elastic. No peeling or flaking. Adheres well to thin coatings of conventional stain.

Full declaration: Linseed oil, linseed oil - stand oil, linseed oil - wood oil - stand oil, orange oil, Isoaliphates, natural asphalt, linseed oil - stand oil - natural resin ester, iron oxide, earth- and mineral pigments, birch bark extract and drying agents free of lead.

Colours: 041 English red 062 walnut 087 light oak 103 dark brown 051 Persian red 068 light teak 101 black 450 green.

Dilution: Ready to use.

Application method: Brush, dip or spray in dry condition at temperatures above 15°C (59°F) and dry weather conditions.

VARIATION OF USES:

Coverage: One litre (1, 06 fl. quart) covers approximately 10 to 15 m² (107.5 to 161 ft²). Coverage could be considerably less depending upon the condition and absorbency of the surface. Always do a test coating first!

Drying time: At 23°C (73°F) and 50% relative humidity, second coat may be applied after about 24 hours. Apply third and successive coats after 24 to 48 hours.

Cleaning: Clean equipment immediately after use with LEVO Brush Cleaner No. 997

Specific gravity: Approximately 0.90 g/ml (deviations possible depending upon the colour).

Safety advice: Always be sure to store cloths, sponges, etc. that are still wet or even slightly moist with DONNOS Penetrating Fence Stain No. 223 in an airtight metal container or in water, as there is a danger of combustion due to linseed oil content. The product itself is not spontaneously combustible. Contains limonene. R10 Flammable S 2 Keep out of the reach of children S 62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label UN 1263 Water endangerment class WGK 1 (self-assessment)



sales@coloursbynature.com.au

www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550

Disposal: According to locally regulated laws.

Container sizes: 0.75 lt, 2.5 lt; 5 lt; 10 lt; 30 lt; 200 lt

Storage: Cool and dry, please see label for expiry date.

How to use DONNOS Penetrating Fence Stain 223

Preparation of untreated wood: Surface must be dry (less than 15 % wood moisture), solid, able to absorb, clean, and free of dust.

Application: Stir DONNOS No. 223 well before use. Apply three thin coats with a drying time of 24 to 48 hours between each coat. Best working temperature: 15 - 25 °C (59 - 77 °F).

Renovation of porous surfaces: On rough sawn surfaces particles of dust and dirt from the surrounding air may adhere and promote settling of fungi because of special climate conditions. The grey to black discolorations can be removed with GLORIOUS Natural Siding and Masonry Cleaner Nr.1806 and a brush or high pressure cleaner. Clean old coatings and sand if needed. Continue as in first treatment. With timely renovation only a second and/or final coating is necessary.

Renovation of non-porous surfaces: Pore - clogging coatings (oil paints, stains, varnishes, wax coats) must be sanded or stripped to completely remove old residue. Surface must be dry, solid, absorbent, clean and free of dust. Then follow instructions as above for untreated wood.

Important tips: At temperatures above 20 °C (68 °F) product may not dry evenly. At temperatures below 15 °C (59 °F), in rainy or very foggy weather, or when overnight frost is expected, drying delays and unsatisfactory adhesion is possible. DONNOS No. 223 does not contain fungicides. Rough sawn wood is prone to blue-staining fungi. Sand rough surfaces. Treat wood prone to blue-staining fungi and back aired panelling with ADAO External Primer No. 259. To produce an even coating when dipping or spraying, brush lightly after 30 minutes to smooth out the treated surface. Colour variations are possible by mixing with KALDET All Weather Stain No. 270 (boxwood, oak, walnut, Brazil, dark teak, country blue or light grey), or by mixing with VINDO Natural Gloss Paint No. 629 (add max. 5% of any colour except white or ochre). Playground equipment exposed to mechanical wear and tear should get an after treatment with KALDET Transparent Wood Stain No. 270.



sales@coloursbynature.com.au

www.coloursbynature.com.au

Phone: 02 6100 3889 or 1300 249 347

Fax: 02 6492 0502

Address: PO Box 1188 BEGA NSW 2550